

## Buttering system WBS-600







## Buttering system **WBS-600**








## **WBS-600**

- \*The solution for the buttering on a lot of sandwich products
- \* The buttering system for the industrial production
- \* The products are covered by a contact method flatly
- \* The buttering can be carried out with different masses (Ex. mixed butter, mayonnaise mix, sandwich spread)
- \* A continuous product run is carried out
- \* The height of the spread head is individually adjustable on different product heights - automatic compensation at different product heights of (+/- 5 mm.)
- \* The product feed could made by manual or by an automatic product take-over of a conveyor belt
- \* direct regulation of the working speed by potentiometers
- \* The layer thickness is also adjustable Attitude of the layer thickness by handwheel and scale
- \* mobile unit by swivel castors through this the machine can be used flexibly in different production areas
- \* easy dismantling of the most important machine parts for the fast and effective cleaning (Dismantling without tool)



Length: 1300mm Width: 1200mm Height: 1850mm

Weight: app.250 kg

max. working width 600 mm min. product height: 5 mm max. product height: 40 mm

Electr. power:: 230/400V 50 Hz

3 Ph

Power consumption: 1,5 kW



Internet: www.krumbein-rationell.de Tel.: 0049-(0)36259-58015 e-mail: info@krumbein-rationell.de Fax.: 0049-(0)36259-58083